Oblivious Polynomial Evaluation*

Moni Naor† Benny Pinkas‡

Abstract

Oblivious polynomial evaluation is a protocol involving two parties, a sender whose input is a polynomial P, and a receiver whose input is a value α. At the end of the protocol the receiver learns $P(\alpha)$ and the sender learns nothing. We describe efficient constructions for this protocol, which are based on new intractability assumptions that are closely related to noisy polynomial reconstruction. Oblivious polynomial evaluation can be used as a primitive in many applications. We describe several such applications, including protocols for private comparison of data, for mutually authenticated key exchange based on (possibly weak) passwords, and for anonymous coupons.

1 Introduction

A secure computation protocol for a function $f(\cdot,\cdot)$ allows two parties, a receiver who knows x and a sender who knows y, to jointly compute the value of $f(x,y)$ in a way that does not reveal to each side more information than can be deduced from $f(x,y)$. The fact that for every polynomially computable function $f(\cdot,\cdot)$ there exists such a (polynomially computable) protocol is one of the most remarkable achievements of research in foundations of cryptography. However, the resulting protocols are often not as efficient as one would desire, since the number of cryptographic operations that should be performed is proportional to the *size of the circuit computing* $f(x,y)$ [55]. Even for relatively simple functions this may be prohibitively expensive. It is therefore interesting to investigate for which functions it is possible to come up with a protocol that does not emulate a circuit computing the function.

1.1 Oblivious Polynomial Evaluation

In the Oblivious Polynomial Evaluation (OPE) problem the input of the sender is a polynomial P of degree k over some field $\mathcal{F}$. The receiver can get the value $P(x)$ for any element $x \in \mathcal{F}$ without learning anything else about the polynomial P and without revealing to the sender any information about x (for the precise definition of learning and information see Section 1.2). This problem has not been investigated so far; we find it to be a useful

*This paper is the full version of the sections that describe oblivious polynomial evaluation in "Oblivious Transfer and Polynomial Evaluation", 31st STOC, 1999.

†Dept. of Computer Science and Applied Mathematics, Weizmann Institute of Science, Rehovot 76100, Israel. Research supported by grant no. 356/94 from the Israel Science Foundation administered by the Israeli Academy of Sciences. E-mail: moni.naor@weizmann.ac.il.

‡HP Labs Israel. Email: benny.pinkas@hp.com, benny@pinkas.net. Most of this work was done at the Weizmann Institute of Science and was supported by an Eshkol grant of the Israel Ministry of Science.

primitive. For example, as it can act as a cheap replacement for pseudo-random functions in case only k-wise independence is needed.

Strongly polynomial overhead: The overhead of an algorithm is strongly polynomial if it is bounded by a polynomial function of the number of data items in the input, rather than the size of the input values (e.g. the number of bits of numerical input values). The issue of finding protocols for oblivious polynomial evaluation whose overhead does not depend on the field size, might be regarded as being the equivalent of searching for strongly polynomial algorithms in combinatorial optimization (e.g. for linear programming). In the context of cryptographic protocols we measure the overhead in terms of the number of public key operations (i.e. operations based on trapdoor functions) with a specific security parameter, where the size of the inputs to the public key operations is linear in the security parameter. (In the context of this paper, we usually only measure the number of invocations of a 1-out-of-2 oblivious transfer protocol.) Counting only public key operations is justified since the overhead of public key operations depends on the length of their inputs, and is greater by orders of magnitude than the overhead of private key operations (i.e. operations based on one-way functions).

We therefore say that a cryptographic protocol is strongly polynomial if the following two properties hold: (1) the number of public key operations performed by the protocol is bounded by a polynomial function of a security parameter and of the number of inputs (but not their size), and (2) the length of the inputs to the public key operations is linear in the security parameter. Note that the number of *private* key operations that the protocol performs can be polynomial in the size of its inputs.

Oblivious polynomial evaluation can be implemented using general protocols for secure two-party computation [55]. However, these protocols operate on the binary circuit that computes the function and are not strongly polynomial, as the number of oblivious transfers they use is at least linear in $\log \mathcal{F}$, where $\mathcal{F}$ is the field over which the polynomial is defined. A different construction of oblivious polynomial evaluation can be based on using homomorphic encryption (e.g., Paillier's encryption system [50]). That construction, too, is not strongly polynomial, as the size of the input to the homomorphic encryption function must be as long as the receiver's input in the OPE protocol. In contrast, the number of oblivious transfers used by the protocols presented in this paper does not depend on the size of the underlying field: The length of the items transferred in the oblivious transfer protocols is of size $\log |\mathcal{F}|$, but they require only $O(1)$ public key operations per transfer. Namely, if $\log |\mathcal{F}|$ is longer than the length of the input of the OT protocol, then the items to be transferred in the OT protocol are encrypted using random keys, and the corresponding keys are transferred in the actual OT protocol.

Moreover, our protocols can be readily applied to oblivious computation of $g^{P(x)}$, where P is a polynomial, with no increase in their overhead, as described in Section 4.1. In comparison, the binary circuits that evaluate this function must compute exponentiations and are very large, and the overhead of the resulting secure protocols is high. (Protocols based on homomorphic encryption, however, can compute $g^{P(x)}$ without increasing their overhead.) Oblivious evaluation of $g^{P(x)}$ yields k-wise independent outputs that might be useful for distributed implementations of some public key operations.

The noisy polynomial reconstruction problem: The protocols we describe are based on intractability assumptions related to the *noisy polynomial reconstruction problem.*

While being related to other computational problems, this problem has not been used before as an intractability assumptions in a cryptographic protocol. Section 2 describes in detail the assumptions and the background.

Overhead independent of the *degree* of the polynomial: We describe a protocol (Protocol 3.4) whose computational overhead (as measured by the number of 1-out-of-2 oblivious transfers that are computed) is independent of the degree of the polynomial. I.e., for any degree d, the number of oblivious transfers that are required for an oblivious evaluation of a polynomial of degree d is the same as for a linear polynomial. (Of course, the total computation overhead of the evaluation of the polynomial depends on the degree of the polynomial, but the number of public key operations is independent of the degree.)

Applications: We envision two types of applications for oblivious polynomial evaluation. One is whenever k-wise independence can replace full independence or pseudo-randomness (i.e. oblivious evaluation of a pseudo-random function, as in [48]). Such property is required, for example, for the application of constructing anonymous coupons that enable anonymous usage of limited resources (e.g., for constructing an anonymous complaint box). The other type of applications uses OPE for comparing information without leaking it, or preserving anonymity when the receiver must compute the value of a polynomial at a certain point. Applications of this nature include a protocol that allows reliable and privacy preserving metering (described in Section 4.3), a method for distributed generation of RSA keys, designed by Gilboa [26], and a protocol for private computation of the ID3 data mining algorithms [37] (in that case the polynomial is used for a Taylor approximation of the logarithm function).

1.2 Correctness and Security Definitions

We now get to the delicate business of defining the security of oblivious polynomial evaluation. OPE requires privacy for both receiver and sender. Namely, in an OPE protocol neither party learns anything more than is defined by the OPE functionality. The strongest way of formalizing this notion and ensuring simple composability of the protocols is through the definition of secure two-party computation (see, e.g., Goldreich [29]) and papers on universal composability, e.g. [13, 14]). However, this definition is rather complex, while there are many applications that do not require the full power of the general definition and could use "non-ideal" protocols. We therefore prefer to use a relaxed definition for OPE, which ensures privacy for both parties but does not require the sender to commit to its input (i.e., to commit to the polynomial P). We call this definition *private computation.* The definition of private computation is relevant also to the case of malicious parties (and is therefore stronger than a definition for the semi-honest case only). It preserves the privacy of the clients, but does not require one to simulate the joint distribution of the view of a malicious sender and the output of an honest receiver, as is required by the general definition of secure computation.

We claim that this relaxation is justified by efficiency considerations, in particular when constructing specific OPE protocols rather than black-box reductions of OPE to other primitives. Furthermore, the definition of private computation is standard for related primitives such as oblivious transfer [52, 21, 45, 47] or PIR [16, 35] (note that we present a reduction of OPE to oblivious transfer). Note also that the definition of private computation is equivalent to the definition of secure computation in the case of semi-honest parties. Furthermore, we deal with a receiver-sender (a.k.a. client-server) scenario, where only one party, the receiver, has an output in the protocol. Therefore, the two definitions are equivalent with respect to a malicious *client*, as there is no issue of simulating the joint distribution of the client's view and the server's output.

The requirements of a private OPE protocol can be divided into *correctness, receiver privacy,* and *server privacy.* Let us first define these properties independently and then define a private OPE protocol as a protocol satisfying these definitions. In the definitions, the running time of polynomial time algorithms is polynomial in the size of their inputs, as well as in the $\log|\mathcal{F}|$, where $\mathcal{F}$ is the field in which the polynomial P is defined, and in a security parameter k. (Note that the length of representations of elements in $\mathcal{F}$ must be polynomial in the security parameter since otherwise the cryptographic operations might be insecure given adversaries with poly-$\log|\mathcal{F}|$ running time.) We don't require in the definitions themselves that the number of public-key operations is independent of $\mathcal{F}$. To simplify the notation we also omit any reference to auxiliary inputs.

We first define the input and output for the functionality of oblivious polynomial evaluation, as a two party protocol run between a receiver and a sender over a field $\mathcal{F}$.

- **Input**
  - Receiver: an input $x \in \mathcal{F}$.
  - Sender: A polynomial P defined over $\mathcal{F}$.
- **Output**
  - Receiver: $P(x)$.
  - Sender: nothing.

Definition 1.1 (Correctness) *At the end of the protocol the receiver obtains the output of the OPE functionality, namely $P(x)$.*

The definition of the receiver's privacy is simplified by the fact that the sender gets no output. It is as follows:

Definition 1.2 (Receiver's privacy – indistinguishability) *For any probabilistic polynomial time $\mathcal{B}'$ executing the sender's part, for any x and x' in $\mathcal{F}$, the views that $\mathcal{B}'$ sees in case the receiver's input is x and in case the receiver's input is x' are computationally indistinguishable.*

The definition of sender's privacy is a bit trickier, since the receiver (or whatever machine that is substituted for her part) obtains some information, and we want to say that the receiver does not get more or different information than she should. We compare the protocol to the *ideal implementation.* In the ideal implementation there is a trusted third party Charlie, which gets the sender's polynomial P and the receiver's request x and gives $P(x)$ to the receiver. The privacy requirement is that the protocol does not leak to the receiver more information than in the ideal implementation.

Definition 1.3 (Sender's security – comparison with the ideal model) *For every probabilistic polynomial-time machine $\mathcal{A}'$ substituting the receiver, there exists a probabilistic polynomial-time machine $\mathcal{A}''$ that plays the receiver's role in the ideal implementation, such that the view of $\mathcal{A}'$ and the output of $\mathcal{A}''$ are computationally indistinguishable.*

Definition 1.4 (Private OPE protocol) *A two-party protocol satisfying Definitions 1.1, 1.2 and 1.3.*

Note that the definition of receiver privacy does *not* preclude the sender from cheating by using a polynomial of degree higher than the degree of P (and therefore it might not be possible to extract from the sender a degree k polynomial.) We do not require that the sender be committed to single polynomial, and that the receiver could verify that the value she receives corresponds to this polynomial. Our construction allows such cheating; however, in many applications (including the ones described in this paper) this is immaterial.

As a side note we observe that a possible approach for ensuring correctness could use the verifiable secret sharing (VSS) schemes of Feldman and of Pedersen [23, 51], which let the sender commit to a single polynomial P before engaging in the OPE protocol. Since two polynomials of degree d agree in at most d locations, an OPE invocation in which the sender lets the user evaluate a different polynomial P' of the same degree is revealed with probability $1 - d/|\mathcal{F}|$ by a receiver that evaluates the polynomial at a *random* point. This approach does not work, however, if the sender has some information about the distribution of points in which the user might compute P.

1.3 Related Work

1.3.1 Oblivious transfer

The basic cryptographic primitive that is used by the oblivious polynomial evaluation protocols is *oblivious transfer*. The notion of 1-out-2 oblivious transfer was suggested by Even, Goldreich and Lempel [21] as a generalization of Rabin's "oblivious transfer" (OT) [52]. For an up-to-date and erudite discussion of OT see Goldreich [29]. 1-out-of-N Oblivious Transfer was introduced by Brassard, Crépeau and Robert [10, 11] under the name ANDOS (all or nothing disclosure of secrets). They used information theoretic reductions to construct 1-out-of-N protocols from $N-1$ invocations of a 1-out-of-2 protocol (lately it was shown that such reductions must use at least $\Omega(N)$ invocations of 1-out-of-2 OT in order to preserve the information theoretic security [17]).

Constructions of oblivious transfer protocols can be divided to different categories, based on the security definitions that they satisfy:

- OT protocols which provide security in the semi-honest model. These include basic protocols based on the Even-Goldreich-Lempel (EGL) paradigm [21], such as the protocols of Bellare and Micali [6] and generic constructions based on the existence of trapdoor permutations. These protocols can be made secure with respect to malicious parties if we add zero-knowledge proofs in which the parties prove that they follow the protocol. If the zero-knowledge proofs enable extraction then the protocols are simulatable, but only for a single invocation at a time (rather than for parallel or concurrent invocations of the protocol).

- OT protocols which provide information-theoretic security for the sender with respect to a corrupt receiver, and computational security for the receiver (e.g. the two round protocols of [46, 1, 54]). Although these protocols provide information-theoretic security, they do not enable to extract the receiver's input. Therefore they do not enable easy simulation of the output that is obtained by the receiver.

- Fully simulatable OT protocols, in particular for parallel or concurrent invocations. These include the concurrent OT protocol of [24] (which assumes that the inputs are independent), the universally composable protocols of [14], and the universally composable committed OT of [25].

- Protocols based on the random oracle model. In this model it is possible to design very efficient protocols based on the EGL or the Bellare-Micali paradigms. These protocols are secure against malicious parties and fully simulatable. Their security relies, however, on the random oracle model.

Our work builds upon the 1-out-of-N and k-out-of-N oblivious transfer protocols described in [45], which are based on efficient computationally secure reductions to 1-out-of-2 oblivious transfer. A transfer of an input element in these protocols requires $\log N$ invocations of 1-out-of-2 oblivious transfer, and is, therefore, quite efficient. Furthermore, more recent constructions [47] reduce the amortized overhead of oblivious transfer, if multiple invocations of this protocol should be run (as is the case in the OPE constructions). It was also shown recently how to extend oblivious transfer in the sense that two parties can implement a large number of OTs (a number polynomial in k, where k is a security parameter of a pseudo-random function), at the cost of running only k OTs, and executing additional invocations of symmetric cryptographic functions for every OT [34] (this is an efficient realization of a generic construction of Beaver [4]). Security is based on a non-standard assumption (or alternatively on the random oracle assumption), and security against malicious parties is obtained using a cut-and-choose method that involves running multiple invocations of the system. (In our work we measure the computational overhead by the number of OTs that are executed by the parties. The use of this criteria makes sense since all other operations are either arithmetic or symmetric crypto operations, which are considerably more efficient. We present a protocol that uses a minimal number of OTs in the sense that this number is independent of the size of the field and of the degree of the polynomial. When this protocol is invoked many times it might make sense to implement the OTs using the result of [34].)

1.3.2 Secure two-party computation

The idea of secure two-party computation was introduced by Yao [55]. His construction enables one party, the sender, to define a function F and enable another party, the receiver, to compute the value of F at a single point x, without learning anything else about F and without disclosing to the sender any information about x. The construction is based on describing F as a binary circuit, and evaluating the circuit. Its computational overhead is composed of running an oblivious transfer protocol for every input wire of the circuit, and computing a pseudo-random function for every gate. The communication overhead is composed of sending a table, of size linear in the security parameter of the pseudo-random function, for every gate. The overhead, therefore, strongly depends on the size of the representation of F as a binary circuit. In the case of a polynomial of degree d this circuit should compute x^d and its size is $O(|x|^2 \cdot \log |d|)$. In particular, the size of the circuit depends on the size of the field over which the polynomial is defined. (It is also possible to construct a circuit that uses an FFT approach for computing x^d. The size of this circuit, too, depends on the size of the field over which the polynomial is defined.)

In another generic construction, Naor and Nissim [43] show that any two-party protocol can be transformed into a secure protocol with the effect that a protocol with communication complexity of c bits is transformed to a secure protocol which performs c invocations of oblivious transfer (or SPIR) from a database of length 2^c. A simple insecure protocol for oblivious polynomial evaluation has a single round and a communication overhead of $\log |\mathcal{F}|$ bits (the receiver simply sends x to the sender). The result of the Naor-Nissim transformation is a secure protocol that executes an OT/SPIR out of a table of $|\mathcal{F}|$ elements. Namely, the server constructs a table of $|\mathcal{F}|$ items, containing the value of $P(x)$ for every $x \in \mathcal{F}$. The receiver then reads a single entry of this table using OT or SPIR.

2 Intractability Assumptions

This section contains definitions of two new pseudo-randomness assumptions. They are later used for constructing protocols for oblivious polynomial evaluation. The assumptions are closely related to the noisy polynomial reconstruction problem, or the list decoding problem of Reed-Solomon codes. We first describe this well-known problem, and then introduce the pseudo-randomness assumptions.

2.1 The Noisy Polynomial Reconstruction Problem

The noisy polynomial reconstruction problem is described by the following definition:

Definition 2.1 (Polynomial reconstruction)
INPUT: *Integers k and t, and n points $\{(x_i, y_i)\}_{i=1}^n$, where $x_i, y_i \in \mathcal{F}$.*
OUTPUT: *Any univariate polynomial P of degree at most k such that $P(x_i) = y_i$ for at least t values $i \in [1, n]$.*

The noisy polynomial reconstruction problem is related to the list decoding problem, which is motivated by coding theory and was first defined by Elias [20] (and sometimes also termed as the bounded-distance decoding problem). The input to this problem is a received word, and the output is a list of all code words that are within some distance from the received word. For the case of Reed-Solomon codes the list decoding problem can be formulated as follows:

Definition 2.2 (Polynomial list reconstruction)
INPUT: *Integers k and t, and n points $\{(x_i, y_i)\}_{i=1}^n$, where $x_i, y_i \in \mathcal{F}$.*
OUTPUT: *All univariate polynomials P of degree at most k such that $P(x_i) = y_i$ for at least t values $i \in [1, n]$.*

For given values of k and n, and in particular for a given message rate k/n, it is preferable to obtain solutions for minimal values of t. The classical algorithm of Berlekamp and Massey (see e.g. [41]) solves the polynomial list reconstruction problem in polynomial time for $t \geq \frac{n+k}{2}$. Sudan [53] presented a polynomial algorithm that works if $t \geq \sqrt{2kn}$, and later Guruswami and Sudan [32] presented a polynomial algorithm that solves the problem for $t \geq \sqrt{kn}$, and thus improves upon the Berlekamp-Massey algorithm for every value of the message rate k/n.

The "polynomial list reconstruction" problem is defined as a worst case problem regarding the *number* of polynomials that might appear in the solution list. In other words, the definition requires that all polynomials within a given distance be listed. Goldreich et. al. [30] have shown that for $t > \sqrt{kn}$ the number of possible polynomials in the solution to the problem is bounded by a polynomial in n. We are more interested in the problem of finding just a single polynomial that fits t or more of the given n points, since our constructions use random instances for which it holds with high probability that the corresponding instances of the noisy polynomial reconstruction problem have a single solution.

We note that given an input to a noisy polynomial reconstruction problem it is possible to randomize it to obtain an input that corresponds to a random polynomial. Specifically, for parameters k and t and given n points $\{(x_i, y_i)\}_{i=1}^{n}$ the randomization is achieved by choosing a random polynomial R of degree k and constructing a new instance of the problem with input $\{(x_i, y_i + R(x_i))\}_{i=1}^{n}$. While this is by no means a reduction from the worst case problem to the average case (since it only randomizes the polynomial but not the noise), it might hint that solving the problem in the average case might not be much simpler than solving it in the worst case.

2.2 The Intractability Assumptions – Pseudo-randomness

We present two new intractability assumptions. The first assumption is equivalent to a conjecture that given a randomly chosen input to the polynomial list reconstruction problem the value of the polynomial at $x = 0$ is pseudo-random. The second assumption states that the value $P(0)$ is pseudo-random even given some additional hints about the location of the values of P. Section 3 describes OPE protocols that are based on the assumptions.

The intractability assumptions depend on the following parameters:

- $\mathcal{F}$, the field over which the polynomial is defined.
- k, the degree of the hidden polynomial.
- n, the number of correct values of the polynomial, which is also the number of queries made in the oblivious evaluation protocol. (This parameter corresponds to "t" in the definition of the polynomial list reconstruction problem, Definition 2.2. We change the notation to agree with the notation used later in this paper.)
- m, the expansion ratio (namely, the ratio between the total number of points and n). (This parameter corresponds to n/t in Definition 2.2.)

Setting precise parameter sizes to satisfy the intractability assumptions is beyond the scope of this paper, and we therefore do not make any precise recommendations with regard to parameter sizes.

The first intractability assumption

This intractability assumption simply assumes that given an input to the polynomial list reconstruction problem, with all x_i being distinct, the value of the polynomial at $x = 0$ is pseudo-random. I.e., it is infeasible to distinguish between two such inputs corresponding to polynomials with different values at $x = 0$. To define this more formally, we use the following notation:

Let $A_{n,m}^{k,\alpha}$ denote the probability distribution of sets generated in the following way:

1. Pick a random polynomial P over $\mathcal{F}$, of degree at most k, for which it holds that $P(0) = \alpha$.
2. Generate nm random values $x_1, \ldots, x_{nm}$ in $\mathcal{F}$ subject to the constraint that all x_i values are distinct and different from 0.
3. Choose a random subset S of n different indices in $[1, nm]$, and set $y_i = P(x_i)$ for all $i \in S$. For every $i \notin S$ set y_i to be a random value in $\mathcal{F}$.
4. Output the set $\{(x_i, y_i)\}_{i=1}^{nm}$.

The pseudo-randomness assumption is based on the notion of computationally indistinguishability, as defined by Goldreich in [28, page 104]. It sets the size of the parameters to be polynomial in a security parameter ℓ, and requires that the resulting probability ensembles are computationally indistinguishable.

Definition 2.3 (Pseudo-randomness assumption 1) *Let ℓ be a security parameter, and let $n(\ell), m(\ell), k(\ell), F(\ell)$ be polynomially bounded functions that define the parameters n, m, k and the size in bits of the representation of an element in the field $\mathcal{F}$. Let $\mathcal{A}_{n,m}^{k,\alpha}$ and $\mathcal{A}_{n,m}^{k,\alpha'}$ be random variables that are chosen according to the distributions $A_{n,m}^{k,\alpha}$ and $A_{n,m}^{k,\alpha'}$, respectively. Then it holds that for every $\alpha, \alpha' \in \mathcal{F}$ the probability ensembles $\{\mathcal{A}_{n,m}^{k,\alpha}\}$ and $\{\mathcal{A}_{n,m}^{k,\alpha'}\}$ are computationally indistinguishable for adversaries whose running time is polynomial in the security parameter ℓ.*

Pseudo-randomness assumption 1 is related to the assumption that polynomial list reconstruction is hard. Assumption 1 is stronger, since in addition to assuming that reconstructing the polynomial is hard, it assumes that all x_i are distinct and that it is even hard to learn information about the value of the polynomial at 0.

Assumption 1 is weaker than an assumption that states that it is hard to distinguish between any probability ensemble $\{\mathcal{A}_{n,m}^{k,\alpha}\}$ and a probability ensemble that generates sets with the same number of *random* (x, y) values. If the latter assumption is true then so is Assumption 1. (Assume that Assumption 1 does not hold. Then there is a distinguisher such that the probability of its output being 1 given an input from $\{\mathcal{A}_{n,m}^{k,\alpha}\}$ has a non-negligible difference from the probability of it having a 1 output given an input from $\{\mathcal{A}_{n,m}^{k,\alpha'}\}$. The probability of a 1 output given an input from the "random" ensemble must have a non-negligible difference from at least one of these two probabilities.) The converse might not be true. It might be that it is easy to distinguish between an input from the "random" ensemble and an input from $\{\mathcal{A}_{n,m}^{k,\alpha}\}$, but yet for all α values, the inputs from the different $\{\mathcal{A}_{n,m}^{k,\alpha}\}$ ensembles are indistinguishable.

The pseudo-randomness assumption is of course false for any choice of parameters for which the polynomial list reconstruction problem is easy, e.g. when $m < n/k$. (This corresponds to the number of correct points, n, being more than the square root of the total number of points, nm, times the degree of polynomial, k. This equation therefore agrees with the threshold for which the noisy polynomial problem is easy.) In the other direction, it is an open problem to find a reduction from the polynomial list reconstruction to the assumption.

The second intractability assumption

The second assumption states that given n sets with m points in every set, such that a polynomial P agrees with at least one point in each set, the value of $P(0)$ is pseudo-random. Namely, the total number of points, and the number of correct points, are as in Pseudo-randomness assumption 1, but in addition there is a partition into sets and it is promised that the polynomial P agrees with at least one point in each set. It is hard to come up with a reduction to this assumption from Pseudo-randomness assumption 1 since the reduction must map each of the n points of P into a different set. The new assumption seems stronger than Pseudo-randomness assumption 1 since the problem is easier. Namely, the adversary is given an additional hint — the partition into sets containing at least one correct value of the polynomial.

The definition of the assumption uses the following notation.

Let $C^{k,\alpha}_{n,m}$ denote the probability distribution of sets generated in the following way:

1. Pick a random polynomial P over $\mathcal{F}$, of degree at most k, for which it holds that $P(0) = \alpha$.
2. Generate nm random values $x_1, \ldots, x_{nm}$ in $\mathcal{F}$ subject to the constraint that all x_i values are distinct and different from 0.
3. Choose a random subset S of n different indices in $[1, nm]$, and set $y_i = P(x_i)$ for all $i \in S$. For every $i \notin S$ set y_i to be a random value in $\mathcal{F}$.
4. Partition the nm (x_i, y_i) pairs to n random subsets subject to the following constraints:
   - The subsets are disjoint.
   - Each subset contains exactly one pair whose index is in S (and therefore for this pair it holds that $y_i = P(x_i)$).
   - Each subset contains exactly $m-1$ pairs whose indices are not in S (and therefore have a random y_i value).

   Output the resulting subsets.

The intractability assumption says that for any α, α' the two probability ensembles $\{C^{k,\alpha}_{n,m}\}, \{C^{k,\alpha'}_{n,m}\}$ are computationally indistinguishable. It depends on the parameters $\mathcal{F}, k, m$, and n.

Definition 2.4 (Pseudo-randomness assumption 2) *Let ℓ be a security parameter, and let $n(\ell), m(\ell), k(\ell), F(\ell)$ be polynomially bounded functions that define the parameters n, m, k and the size in bits of a representation of an element in the field $\mathcal{F}$. Let $\mathcal{C}^{k,\alpha}_{n,m}$ and $\mathcal{C}^{k,\alpha'}_{n,m}$ be random variables that are chosen according to the distributions $C^{k,\alpha}_{n,m}$ and $C^{k,\alpha'}_{n,m}$, respectively. Then it holds that for every $\alpha, \alpha' \in \mathcal{F}$ the probability ensembles $\{\mathcal{C}^{k,\alpha}_{n,m}\}$ and $\{\mathcal{C}^{k,\alpha'}_{n,m}\}$ are computationally indistinguishable.*

As with the previous assumption there is an easy reduction from the problem of breaking this pseudo-randomness assumption to the noisy polynomial reconstruction problem. In addition, if Pseudo-randomness assumption 1 does not hold in the worst case, then Pseudo-randomness assumption 2 does not hold in the worst case (since any input for the latter can be transformed to an input for the first assumption by simply ignoring the partition into subsets). This reduction is also true in the average case: consider all sets generated by the distributions $A^{k,\alpha}_{n,m}$ and $C^{k,\alpha}_{n,m}$ subject to the constraint that no more than n points in a set agree with the polynomial P (the probability that this property does not hold for a specific set is at most $n(m-1)/|\mathcal{F}|$, which we consider to be negligible). Denote the resulting collections of sets as $\hat{A}^{k,\alpha}_{n,m}$ and $\hat{C}^{k,\alpha}_{n,m}$. Then each of the sets in $\hat{A}^{k,\alpha}_{n,m}$ is mapped to the same number of sets in $\hat{C}^{k,\alpha}_{n,m}$, and no two sets in $\hat{A}^{k,\alpha}_{n,m}$ are mapped to the same set in $\hat{C}^{k,\alpha}_{n,m}$. Now, given a random set in $\hat{C}^{k,\alpha}_{n,m}$, removing the partition into subsets results in a set in $\hat{A}^{k,\alpha}_{n,m}$. Therefore, this procedure has the same probability of hitting any set in $\hat{A}^{k,\alpha}_{n,m}$.

It is an interesting open problem to provide a reduction to Pseudo-randomness assumption 2 from Pseudo-randomness assumption 1, or from the polynomial reconstruction problem. The problem with designing such a reduction is that its output should comply with the input distribution of Pseudo-randomness assumption 2, namely in each subset there should be (with high probability) a single value of the polynomial P.

A remark: The pseudo-randomness assumption that was used in an earlier version of this work [45] was broken by Bleinchenbacher and Nguyen [8] and by Boneh [9]. The assumption was similar to Pseudo-randomness assumption 2, but with the additional requirement that in each subset of the sets generated by $C^{k,\alpha}_{n,m}$ all the points have the *same x coordinate*. This property enables to reduce this problem to an instance of the lattice shortest vector problem, and solve it using the LLL algorithm [36]. We remark that it is unknown how to employ this attack against Pseudo-randomness assumption 2. Furthermore, the overhead of the oblivious evaluation scheme that is based on Pseudo-randomness assumption 2 is not greater than that of the scheme that is based on the broken assumption.

3 Protocols for Oblivious Polynomial Evaluation

This section describes protocols for oblivious evaluation of polynomials. We first describe a generic OPE protocol, and then describe two protocols that implement the generic protocol using each of the two pseudo-randomness assumptions.

We first describe Protocols 3.1, 3.2 and 3.3, which provide privacy against semi-honest or malicious senders, and against semi-honest receivers. Such receivers follow the operation that they should take according to the protocol, but might try to deduce more information from the data they learn in the execution of the protocol. If the polynomial P that is evaluated is linear then the protocols are secure even against malicious receivers. For the case of polynomials P with degrees larger than 1, the protocols ensure that a malicious receiver learns at most a single linear equation of the coefficients of the polynomial, but this equation might not correspond to a legitimate value of the polynomial. We then describe Protocol 3.4 which is secure against malicious receivers. Furthermore, although Protocol 3.4 is a little more complicated conceptually, its computational overhead is better than that of the previous protocols: The number of oblivious transfers, which is the main computational overhead, is independent of the degree of the polynomial P that is evaluated and is equal to the number of oblivious transfers that are required in the case of a linear polynomial.

3.1 A Generic Protocol

All the protocols involve a receiver A and a sender B and have the following specifications:

- Input:
  - *Sender:* a polynomial $P(y) = \sum_{i=0}^{d_P} b_i y^i$ of degree d_P in the field $\mathcal{F}$. (To simplify the notation we denote by y the input to P.)
  - *Receiver:* a value $\alpha \in \mathcal{F}$.
- Output:
  - *Sender:* nothing.
  - *Receiver:* $P(\alpha)$.
- Protocol security parameters: m, k, which are discussed below.

At the end of the protocol the parties learn nothing but their specified outputs. The generic protocol (Protocol 3.1) is described in Figure 1. It is based on the sender hiding P in a *bivariate* polynomial, and running oblivious transfer protocols with the receiver to reveal to her just enough information to enable the computation of $P(\alpha)$. (In this respect, the protocol is somewhat similar to the instance hiding construction of [5, 38].)

The only step that has to be further specified is the third step, in which the receiver learns $d_R + 1$ values of R. This is the only step that involves interaction between the two parties, and as such determines the overhead of the protocol. This step can be based on any of the pseudo-randomness assumptions. Below are descriptions of two protocols for oblivious polynomial computation in which Step 3 is based on each of the two pseudo-randomness assumptions.

3.2 Detailed Protocols

3.2.1 A protocol based on Pseudo-randomness assumption 1

The first protocol employs an n-out-of-N oblivious transfer protocol (see e.g. [45]) to let the receiver learn n values of R while hiding these values from the sender. (See Figure 4.)

Protocol 3.1 (A generic protocol for oblivious polynomial evaluation)

1. **The sender hides P in a bivariate polynomial:** *(see Figure 2) The sender generates a random masking polynomial $P_x(x)$ of degree d, s.t. $P_x(0) = 0$. Namely $P_x(x) = \sum_{i=1}^{d} a_i x^i$. The parameter d equals the degree of P multiplied by the security parameter k (i.e., $d = k \cdot d_P$).*

   The sender then defines a bivariate polynomial

   $$Q(x, y) = P_x(x) + P(y) = \sum_{i=1}^{d} a_i x^i + \sum_{i=0}^{d_P} b_i y^i$$

   for which it holds that $\forall y \;\; Q(0, y) = P(y)$. (Note that Q is defined by only $d + d_P + 1$ coefficients, whereas a random bivariate polynomial of the same degrees is defined by $(d+1)(d_P+1)$ coefficients).

2. **The receiver hides α in a univariate polynomial:** *(see Figure 3) The receiver chooses a random polynomial S of degree k, such that $S(0) = \alpha$. The receiver's plan is to use the univariate polynomial $R(x) = Q(x, S(x))$ in order to learn $P(\alpha)$: it holds that $R(0) = Q(0, S(0)) = P(S(0)) = P(\alpha)$ and, therefore, if the receiver is able to interpolate R she can learn $R(0) = P(\alpha)$. The degree of R is $d_R = d = k \cdot d_P$.*

3. **The receiver learns points of R:** *The receiver learns $d_R + 1$ values of the form $\langle x_i, R(x_i) \rangle$.*

4. **The receiver computes $P(\alpha)$:** *The receiver uses the values of R that it learned to interpolate $R(0) = P(\alpha)$.*

Figure 1: A generic protocol for oblivious polynomial evaluation

Protocol 3.2 (Oblivious polynomial evaluation based on assumption 1) *The protocol is the generic protocol (Protocol 3.1), where the third step is run as follows:*

- *The receiver sets $n = d_R + 1 = d + 1 = kd_P + 1$ and chooses $N = nm$ distinct random values $x_1, \ldots, x_N \in \mathcal{F}$, all different from 0.*

- *The receiver chooses a random set T of n indices $1 \leq i_1, i_2, \ldots, i_n \leq N$. She then defines N values y_i, for $1 \leq i \leq N$. The value y_i is defined as $S(x_i)$ if i is in T, and is a random value if $\mathcal{F}$ otherwise.*

- *The receiver sends the N points $\{(x_i, y_i)\}_{i=1}^{N}$ to the sender.*

- *The receiver and sender execute an n-out-of-N oblivious transfer protocol, for the N values $Q(x_1, y_1), \ldots, Q(x_N, y_N)$. (The receiver chooses to learn $\{Q(x_i, y_i)\}_{i \in T}$.)*

The correctness of the protocol is based on observing that the receiver can learn $d_R + 1$ values of the polynomial R, and can, therefore, interpolate R and compute $R(0) = P(\alpha)$. We prove the security of the protocol in Section 3.3 below.